



-GITRAL®-



HYDROBLUE



Vases pour eau potable (chaude ou froide).
Aucun contact entre l'eau et l'acier grâce à une couche interne en époxy alimentaire. Evite les pertes d'eau chaude. Raccord émaillé.
Parfaitement adaptés pour le pompage et la surpression.
L'installation d'un vase sanitaire permet d'économiser de l'eau, d'allonger la durée de vie des groupes de sécurité attaqués par le calcaire. Les vases sanitaires sont très utiles quand le ballon d'eau chaude est situé en dessous du réseau d'évacuation.

The HYDROBLUE tanks supply the highest feature for drinking and pumping settings.
The food diaphragm membrane prevents bacterial growth and split the water from air. The rest of the water contact is guaranteed by a proper internal epoxy which coats the internal water side including the outlet connection whereas avoiding rust. Wide range (up to 600l) and regular pressure.

Code Article	Reference	Capacité Capacity (litre)	Hauteur Height H (mm)	Diamètre Diameter A (mm)	Raccord Water connection (male)	Pression de pré-gonflage Precharge pressure
11A0000524	HYB5	5	320	160	3/4"	3
11A0000840	HYB8	8	330	200	3/4"	3
11A0001228	HYB12	12	314	270	3/4"	2
11A0001838	HYB18	18	400	270	3/4"	2
11A0002441	HYB24	24	440	300	1"	2
11A0002453	HYB24H	24	440	300	1"	2
11A0003511	HYB35	35	380	380	1"	2

HYB5 => HYB35



HYB24H



Max. working pressure
Pression maxi

10 bar

Working temperature
T° min/T° Max

-10°/ +99°C

Color of tanks
Couleur

BLUE



HYDROBLUE



Vases pour eau potable (chaude ou froide).
Aucun contact entre l'eau et l'acier grâce à un
couche interne en époxy alimentaire. Evite les pertes
d'eau chaude. Raccord émaillé.
Parfaitement adaptés pour le pompage et la
surpression.
L'installation d'un vase sanitaire permet
d'économiser de l'eau, d'allonger la durée de vie
des groupes de sécurité attaqués par le calcaire.
Les vases sanitaires sont très utiles quand le ballon
d'eau chaude est situé en dessous du réseau
d'évacuation.

The HYDROBLUE tanks supply the highest feature
for drinking and pumping settings.
The food diaphragm membrane prevents bacterial
growth and split the water from air. The rest of the
water contact is guaranteed by a proper internal
epoxy which coats the internal water side including
the outlet connection whereas avoiding rust. Wide
range (up to 600l) and regular pressure.

Code Article	Reference	Capacité Capacity (litre)	Hauteur Height H (mm)	Diamètre Diameter A (mm)	Raccord Water connection (male)	Pression de pré-gonflage Precharge pressure
11A0005023	HYB50 V	50	418	380	1"	2
11A0005024	HYB50 H	50	525	380	1"	2
11A0008016	HYB80	80	628	450	1"	2
11A0010517	HYB105	105	685	500	1 1/4"	2
11A0015011	HYB150	150	917	500	1 1/4"	2
11A0020010	HYB200	200	832	600	1 1/4"	2
11A0025008	HYB250	250	977	630	1 1/4"	2
11A0030010	HYB300	300	1125	630	1 1/4"	2
11A0040009	HYB400	400	1470	630	1 1/4"	2
11A0050004	HYB500	500	1360	750	1 1/4"	2
11A0060005	HYB600	600	1575	750	1 1/4"	2

HYB80 = > HYB600

Max. working pressure Pression maxi	10 bar
Working temperature T° min/T° Max	-10°/ +99°C
Color of tanks Couleur	BLUE

